

High Voltage Isolated MOSFET Driver

Ordering Information

Package Options	
8-Pin Narrow Body SOIC	8-Pin Plastic DIP
HT0440LG	HT0440N4

Features

- ☐ $\pm 400\text{V}$ input to output isolation
- ☐ $\pm 700\text{V}$ isolation between outputs
- ☐ No external voltage supply required
- ☐ Dual isolated output drivers
- ☐ Option of internal or external clock

Applications

- ☐ Telecommunications
- ☐ Modems
- ☐ Solid state relays
- ☐ High side switches
- ☐ High end audio switches
- ☐ Avionics
- ☐ ATE

Absolute Maximum Ratings


Input to Output Isolation Voltage, V_{ISO}	$\pm 400\text{V}$
Logic Input Voltage, V_A, V_B	-0.5 to $+7.0\text{V}$
Operating Temperature	-40°C to $+85^\circ\text{C}$
Storage Temperature	-55°C to $+150^\circ\text{C}$

Note: All voltages are referenced to ground.

General Description

The Supertex HT0440 is a dual high voltage isolated driver utilizing Supertex's proprietary HVC MOS[®] technology. It is designed to drive discrete MOSFETs configured as bidirectional or unidirectional switches. It can drive N-channel MOSFETs as high side switches up to 400V. The HT04 has an internal clock which generates two independent DC isolated voltages to the outputs, V_{OUTA} and V_{OUTB} when logic inputs A and B are at logic high. The internal clock can be disabled by applying an external clock signal to the CLK pin. This allows the power dissipation and AC characteristics to be tailored to meet specific needs. The HT04 does not require any external power supplies. The internal supply voltage is supplied by either of the two logic inputs A or B when they are at logic high.

Pin Configuration



1/26/94

Supertex Inc. does not recommend the use of its products in life support applications and will not knowingly sell its products for use in such applications unless it receives an adequate "products liability indemnification insurance agreement." Supertex does not assume responsibility for use of device described and limits its liability to the replacement of devices determined to be defective due to workmanship. No responsibility is assumed for possible omissions or inaccuracies. Circuitry and specifications are subject to change without notice. For complete liability information covering this and other Supertex products, refer to the Supertex 1993-94 Databook.

Electrical Characteristics

(over recommended operating conditions, $T_A = 25^\circ\text{C}$ unless otherwise specified)

DC Characteristics

Symbol	Parameter	Min	Typ	Max	Unit	Conditions
I_{IHA}, I_{IHB}	Logic high input current (per input)			500	μA	$V_A = 3.5\text{V}, V_B = 3.5\text{V}, \text{CLK} = 0\text{V}$
				250	μA	$V_A = 3.5\text{V}, V_B = 3.5\text{V}, \text{CLK} = 500\text{KHz}$
				1.0	mA	$V_A = 3.5\text{V}, V_B = 3.5\text{V}, \text{CLK} = 2.0\text{MHz}$
				2.0	mA	$V_A = 5.5\text{V}, V_B = 5.5\text{V}, \text{CLK} = 0\text{V}$
				1.0	mA	$V_A = 5.5\text{V}, V_B = 5.5\text{V}, \text{CLK} = 500\text{KHz}$
V_{OUTA}, V_{OUTB}	Output Voltage	6.0			V	$V_A = 3.15\text{V}, V_B = 3.15\text{V}, \text{CLK} = 0\text{V}, \text{no load}$
		5.0			V	$V_A = 3.15\text{V}, V_B = 3.15\text{V}, \text{CLK} = 500\text{KHz}, \text{no load}$
		6.0			V	$V_A = 3.15\text{V}, V_B = 3.15\text{V}, \text{CLK} = 2.0\text{MHz}, \text{no load}$
		10.0			V	$V_A = 4.5\text{V}, V_B = 4.5\text{V}, \text{CLK} = 0\text{V}, \text{no load}$
		8.0			V	$V_A = 4.5\text{V}, V_B = 4.5\text{V}, \text{CLK} = 500\text{KHz}, \text{no load}$
I_{ILA}	Logic low input A current			10	μA	$V_A = 0.5\text{V}, V_B = \text{high}$
I_{ILB}	Logic low input B current			10	μA	$V_A = \text{high}, V_B = 0.5\text{V}$
I_{ILQ}	Quiescent current			10	μA	$V_A = 0.5\text{V}, V_B = 0.5\text{V}$
V_{ISO}	Input to output isolation voltage	± 400			V	
V_{CISO}	Output to output isolation voltage	± 700			V	

AC Characteristics

Symbol	Parameter	Min	Typ	Max	Unit	Conditions
$t_{d(ON)}$	Turn on delay time			50	μs	See timing diagram and test circuit $\text{CLK} = 0\text{V}, C_L = 600\text{pF}$
t_r	Rise time			650	μs	
$t_{d(OFF)}$	Turn off delay time			150	μs	
t_f	Fall time			3.0	ms	

Recommended Conditions


Symbol	Parameter	Min	Typ	Max	Unit	Conditions
CLK	External clock frequency	0.5		2.0	MHz	
V_{IHCLK}	Clock input high voltage	3.15		5.5	V	
V_{ILCLK}	Clock input low voltage	0		0.5	V	
V_{IH}	Logic input high voltage	3.15		5.5	V	
V_{IL}	Logic input low voltage	0		0.5	V	
T_A	Operating temperature	-40		+85	$^\circ\text{C}$	

Truth Table*


A	B	CLK	V _{OUTA}	V _{OUTB}	Internal Clock
0	0	0	Off	Off	Off
0	1	0	Off	On	On
1	0	0	On	Off	On
1	1	0	On	On	On
0	0	Clk	Off	Off	Off
0	1	Clk	Off	On	Off
1	0	Clk	On	Off	Off
1	1	Clk	On	On	Off

*CLK pin must be connected to ground when the internal clock is required.

Block Diagram



Timing Diagram



Test Circuit

